LİTHĪUMVALLEY



Residential LFP Battery Series

LV-BAT-W5.12Ac

51.2V 100Ah 5.12kWh

A sleek and space-saving solution for your energy storage needs. With its compact design and easy installation, it seamlessly blends into any environment. Whether in your home, office, or commercial space, our wall-mounted unit provides reliable and efficient energy storage.







LV-BAT-W5.12Ac is a perfect wall-mounted solar energy lithium battery for residential home use. Built-in with High-Quality LiFePO4 large capacity cells. It ensures a long cycle life of the battery system. The designed BMS is verified to be compatible with different brands of inverters, hybrid on grid&off grid or off grid.

DONGUAN
LITHIUM VALLEY
ENERGY CO., LTD.

FEATURES



Unique Design

New wall mount design



Flexible Capacity

Max.15pcs in Parallel to extend capacity



Safe &Reliable

Lithium Iron Phosphate (LFP) Cell



LED Display

SOC, Battery Status



Easy Installation


Quick plug in +/- and parallel connection



Certificates

CB, IEC62619, UL1973, UKCA, CE-EMC, CE-GPSD, EN62619; UN38.3, MSDS

Dimensions







Model	LV-BAT-W5.12Ac
ominal Voltage	51.2V
Pated Capacity	100Ah
nergy	5120Wh
Charging Cut-off Voltage	56.16 V
oischarge Cut-off Voltage	45.6 V
Recommend charge/discharge current	50A
Maximum continuous charge/discharge current	100A
nstantaneous discharge current	200A/3S
Charge temperature	0~55°C
Discharge temperature	-20~60°C
torage Environment 50% state of charge)	20°C ~ 45°C in three months; 25±3°C over three months; Humidity:65±20%RH
nvironment	Indoor/outdoor under roof (avoid direct sunlight)
nstallation	Wall mounted
ell Technology	Lithium iron phosphate (LiFePO4)
fe Cycle	6000 times @80%DOD
ooling	Natural convection
rotection Rating	IP65
ertificates	CB, IEC62619, UL1973, UKCA, CE-EMC, CE-GPSD, EN62619 ; UN38.3, MSDS
Dimension and Weight	
imension	520*470*141.5mm
attery Net Weight/Gross Weight	48.45KG/54.15KG
communication Instruction	
ommunication	RS232, CAN, RS485

^{*}The actual product may have slight differences from some promotional videos or pictures. Please refer to the actual product. Unless otherwise specified the data on this page are all from our company's laboratory. The data may have errors due to changes in the objective environment.

^{*}The specifications are subject to change without prior notice.













